

RC16 4K Ultra HD USB Camera



Ultra-high definition and ultra-large field of view

Equipped with a new generation of UHD CMOS image sensor, it has more accurate native resolution, richer color information, four times the effect of HD image, and shoots 4K video with full details. With a 110-degree ultra-large Angle and low distortion 4K lens, the panoramic view is unobtrusive.

USB 3.0

Full-function USB 3.0 interface, power supply, video, audio in one, can also support 2 USB video signal source (optional)+1 channel audio source at the same time.

The wave speed forms a microphone array

Built - in beamforming microphone array, unique noise suppression algorithm and automatic gain algorithm, pick up distance up to 6 meters, make your speech perfect presentation.

AI ability

Multi-layer convolutional neural network design, cutting-edge deep learning algorithms, enabling intelligent features of the camera, high quality analysis data can be accessed through open APIs.

Auto Framing

The advanced deep learning algorithm is adopted to automatically adjust the size of the picture Angle according to the people in the detection field of vision, eliminating the need for manual adjustment of camera operation, bringing you a new intelligent experience.

AI humanoid tracking

Embedded NNE hardware unit, using deep learning technology, through the extraction of target features, no matter where the face is facing, can achieve smooth humanoid tracking, suitable for automatic speaker tracking and other application scenarios.

Convenient operation

With exquisite infrared remote control and exclusive software, automatic box selection and humanoid tracking can be started with one button, and preset position, EPTZ, image parameters can be set at the same time.

Camera	
Sensor	1/2.7", CMOS, Effective Pixel: 8.29M
Scanning Mode	Progressive
Lens Mount	M12
Lens	Focus: f=2.2mm, FOV: 110°
Digital Room	8X
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual
Camera bracket	Bracket with damper
Digital Noise Reduction	2D,3D digital noise reduction
Backlight Compensation	Support



General specification	
Input Voltage	5V (USB power supply)
Current Consumption	600mA(MAX)
Operating Temperature	0°C ~ 40°C
Storage Temperature	-40°C ~ 60°C
Power Consumption	3.0W(MAX)
Size	118mm x37.2mm x 30.8mm (Bracket not included)
Net Weight	0.2KG
WTFB	30000h



USB Feature	
Operate System	Windows® 7 (1080P and under only), Windows 8.1, Windows 10 or higher macOS™ 10.10 or higher Google™ Chromebook™ Version 29.0.1547.70 or higher Linux (support UVC)
Hardware Requirement	2.4 GHz Intel® Core 2 Duo processor or higher;2 GB RAM or higher USB 2.0 interface
Color System / Compression	H.264 / MJPEG /YUY2 /NV12
Video Format	4k@30fps/25fps, 1080p@30fps/25fps, 720p@30fps/25fps, 960x540p@30fps/25fps, 640x360p@30fps/25fps etc
USB Video Communication Protocol	UVC 1.1
UVC PTZ	Support(EPTZ)



Input/Output Interface	
USB Interface	1xUSB 3.0: Type-C, female
IR remote	support